

Product Information


DMR21 Series 2-Wire Outdoor Station



DESCRIPTION

2-wire apartment system color fisheye camera modularity outdoor station.

DIMENSION





FEATURES

- Full 304 stainless steel panel
- 170° fisheye high resolution camera
- Synthesis language reminder
- Large capacity(max.128 apartments via BDU)
- Reliable proximity access
- Colorful LED for work status indicators
- Diverse module configurations
- Nameplate or name list via TFT modular
- Support 2nd lock via DT-RLC
- Only support flush mounting;
- Anti-tamper screw installation;
- Compatible with all DT two wire system models.



1. Parts and Functions




Embedded box

Front panel

Note:Key A and key B will not be seen on the panel,they are cryptic.About activating key A and key B, please refer to the user manual.

2. Terminal Description



+12V: 12VDC power output.

LK-: power ground.

LK+: common contact of the relay.

NO.: normally open contact of the relay(refer to DT technical guide for Lock connection detail informations).

EB+: exit button positive connection port.

EB-: exit button negative connection port.

JP-LK: for electronic lock safety type setting (refer to door lock connections).

SET : DIP switches for system configurations.

CN/KMB: call button module connection port.

CN/T-COIL: reserved.


CN/FUN: touch sensor keypad module or TFT display module connection port.

CN/WGN: card reader module connection port.

Bus(L1,L2): non-polarity bus line,connect to PC6A(power comb unit).


3. Mounting

Standard mounting





Expanding panel mounting



4. Specification

- Power supply:** 24Vdc(supplied by PC6A)
- Camera:** 1/2.7" fisheye camera,170° wide angle
- Power Consumption:** 1W in standby
5W in working
- Unlock Power output:** 12Vdc,250mA
- Unlock timing:** 1~99s
- Working temperature:** - 20°C ~ +55°C
- Screen:** 3.5 inch TFT(with TFT module)
- Resolution:** 320(R, G, B)X240 pixels(TFT module)
- Wiring:** 2 wires (non-polarity)
- Dimension:** 316(H)×133(W)×48(D)mm

5. Ordering Information

Model No.	Description	Remark
DMR21/S8-FE	Color fisheye camera outdoor station (8 buttons,single row)	NSTC,PAL must be specified
DMR21/D16-FE	Color fisheye camera outdoor station (16 buttons,doube row)	NSTC,PAL must be specified
DMR21/ID/S4-FE	Color fisheye camera outdoor station with proximity access control (4 buttons,single row)	NSTC,PAL must be specified
DMR21/ID/D8-FE	Color fisheye camera outdoor station with proximity access control (8 buttons,double row)	NSTC,PAL must be specified
DMR21/S4/F1-FE	Color fisheye camera outdoor station with one dummy panel (4 buttons,single row)	NSTC,PAL must be specified
DMR21/D8/F1-FE	Color fisheye camera outdoor station with one dummy panel (8 buttons,doube row)	NSTC,PAL must be specified
DMR21/F2-FE	Color fisheye camera outdoor station with two dummies panel	NSTC,PAL must be specified
EP21/S12	Extended panel (12 call buttons,single row)	
EP21/D24	Extended panel (24 call buttons,double row)	



6. Packing Information

Single Package



Dimensions: 171(H)X420(W) X98(D) mm


Gross Weight: 1.56Kg

Carton Package




Carton: 265(H)×415 (W)×360(D)mm

Quantity: 7PCS



DMR21/S8-FE



DMR21/D16-FE



DMR21/D/S4-FE



DMR21/D/D8-FE




DMR21/S4/F1-FE




DMR21/D8/F1-FE



DMR21/F2-FE



EP21/S12



EP21/D24

Modules Selection



R21/TFT



R21/LB



R21/D



R21/TK



R21/S4



R21/D8